

10R-1U-W Series – WVR 120V ac Single Phase

Models	10R-1U-15W-I	10R-1U-20W-I
Mfg Part #	002-00142	002-00153
Voltage/Hz	120V ac nominal 50-60 Hz	120V ac nominal 50-60 Hz
Max. Load	15 amps	20 amps
Line Cord	11 ft. 3-wire #14 black SJT, NEMA 5-15P straight plug	8 ft. 3-wire #12 black SJT, NEMA 5-20P straight plug *
Receptacles	4 - NEMA5-15R on rear & 2 - NEMA5-15R on front controlled only by primary switch, 4 - NEMA5-15R on rear controlled by both the primary & secondary switch.	2 - NEMA5-15R and 2 - NEMA5-20R on rear, & 2 - NEMA-5-15R on front controlled only by primary switch, 2 - NEMA5-15R and 2 - NEMA5-20R on rear controlled by both the primary & secondary switch.
Enclosure	Magnetic shielding steel, black powder coat finish	
Weight	9.25 lbs	
Dimensions	1.75"H x 19.0"W x 8.5"D	
Boxed Dim./Wt.	2"H x 21.75"W x 10.75"D, 10.75 lbs	

* **WARNING:** not compatible with standard receptacles, requires NEMA5-20R wall receptacle.



X10 Carrier Current Compatible

3162119

Specifications	
Voltage Ratings	US 120 Volt, single phase (one hot leg & a neutral leg tied to earth ground at service entrance). Will operate over a voltage range of 85 - 175 volts with Spectrum WVR technology (MCOV=175Vac). Full load regulation 1%. Check line wiring for hot/neutral reversal prior to connecting this filter. Hot/neutral building wiring reversal can compromise any appliance's safety and performance.
Operating Temperature Range	0-40 deg. C
Technology	Spectrum WVR® Wide Voltage Range filter technology
Mode	Mode 1 applications, L-N (ground wire protection)
Safety Certifications	CSA 22.2 No. 8-M1986, UL 1283 5 th edition, UL 1363
Limiters	Series surge reactor current limiter; cascaded, auto-tracking dual polarity dynamic surge and noise sensing; bi-modal dynamic filtering. Parameters optimized for switch-mode power supply protection.
Dynamic filtering Onset	172 volts nominal, 2 volts above peak line voltage (auto-tracking- WVR).
Max. Surge Voltage Let-through*	130 Volts above peak line voltage @ 6,000 Volts, 3,000 Amps for ANSI C62.41 Category B3/C1 Combination Wave.
Max. Applied Pulse Voltage	6,000 volts (1.2 x 50 μ s – ANSI C62.41 Combination Wave)
Max. Applied Pulse Current	>100,000 amperes applied (unlimited due to internal current limiting) (8 x 20 μ s).
Joule Rating	Not applicable to this technology. No MOV's to wear out.
Endurance Rating	1,000 worst case pulses: ANSI C62.41, Category B3/C1 pulses (6,000 Volts, 3,000 Amperes); >10,000 pulses at 4,000 Volts; >100,000 pulses at 2,000 Volts.
Filter Slew Rate	5,000 volts/ μ s disturbance reduced to 35 v/ μ s within AC power wave envelope; 5 v/ μ s outside the power wave envelope.
EMI-RFI Filter Response	Bi-directional, wave tracking: With 50 ohm Rgen., load: 7 kHz @ 3 dB; 25 dB @100 kHz; 38 dB @300 kHz.

* Note: Surge voltage let-through is the peak voltage that exceeds the powerline peak voltage.

100% Surge Protection, 0% Failure • Are you Zero Surge protected?

Zero Surge Inc. • 889 State Route 12 • Frenchtown, NJ 08825 • Tel.: 908-996-7700 • Fax: 908-996-7773

URL: www.ZeroSurge.com • Email: info@zerosurge.com

10r_w120_v2_etl.doc