


1R-2U-30T Series – TSC 120V ac Single Phase

Models	1R-2U-30T-120
Mfg Part #	006-00342
Voltage/Hz	120V ac nominal 50-60 Hz
Max. Load	30 amps
Line Cord	30 Amp: 11' grounded 3-wire, #10 black SJT; L5-30P plug. *
Receptacles	one L5-30R outlet on back;
Enclosure	Magnetic shielding steel, black powder coat finish
Weight	16 lbs
Dimensions	3.5”H x 19”W x 10.5”D
Boxed Dim./Wt.	6”H x 22.25”W x 13.0”D, 17 lbs

*** WARNING:** not compatible with standard receptacles, requires NEMA L5-30R receptacle.



X10 Carrier Current Compatible

Specifications	
Voltage Ratings	US 120 Volt, single phase (one hot leg & a neutral leg tied to earth ground at service entrance). Will operate over a voltage range of 85 - 175 volts with Spectrum WVR technology (MCOV=175Vac). Full load regulation 1%. Check line wiring for hot/neutral reversal prior to connecting this filter. Hot/neutral reversal is a critical safety issue and will prevent this product from functioning effectively.
Operating Temperature Range	0-40 deg. C
Technology	TSC Total Surge Cancellation & WVR Wide Voltage Range filter technology
Mode	Mode 1 applications, L-N (ground wire protection)
Safety Certifications	CSA 22.2 No. 8-M1986, UL 1283 5 th edition
Limiters	Series surge reactor current limiter; cascaded, auto-tracking dual polarity dynamic surge and noise sensing; bi-modal dynamic filtering. Parameters optimized for switch-mode power supply protection.
Dynamic filtering Onset	172 volts nominal, 2 volts above peak line voltage (auto-tracking- WVR).
Max. Surge Voltage Let-through*	20 Volts above peak line voltage @ 6,000 Volts, 3,000 Amps for ANSI C62.41 Category B3/C1 Combination Wave.
Max. Applied Pulse Voltage	6,000 volts (1.2 x 50 μs – ANSI C62.41 Combination Wave)
Max. Applied Pulse Current	>100,000 amperes applied (unlimited due to internal current limiting) (8 x 20 μs).
Joule Rating	Not applicable to this technology. No MOV's to wear out.
Endurance Rating	1,000 worst case pulses: ANSI C62.41, Category B3/C1 pulses (6,000 Volts, 3,000 Amperes); >10,000 pulses at 4,000 Volts; >100,000 pulses at 2,000 Volts.
Filter Slew Rate	5,000 volts/μs disturbance reduced to 28 v/μs within AC power wave envelope; 5 v/us outside the power wave envelope.
EMI-RFI Filter Response	Bi-directional, wave tracking: With 50 ohm Rgen., load: 3 dB@ 7kHz; 25 dB @100 kHz; 38 dB @300 kHz.

*Note: Surge voltage let-through is the peak voltage that exceeds the powerline peak voltage.