



8R Series – TSC 120V ac Single Phase

Models	8R15T	8R15T-I	8R20T
Mfg Part #	006-00711	006-00713	006-00721
Voltage/Hz	120V ac nominal 50-60 Hz		
Max. Load	15 amps	15 amps	20 amps
Line Cord	6 ft. 3-wire #14 black SJT, NEMA 5-15P right angle plug		8 ft. 3-wire #12 black SJT NEMA 5-20p straight plug*
Receptacles	8 - NEMA5-15R, 2 always on, 6 switched	8 - NEMA5-15R, 2 always on, 6 switched. Each Duplex receptacle isolated	8- NEMA5-15R, 2 always on, 6 switched
Enclosure	Magnetic shielding steel, black powder coat finish		
Weight	6 lbs		6.5 lbs
Dimensions	4”H x 9”W x 4”D		
Boxed Dim./Wt.	6.5”H x 12”W x 8”D, 8 lbs		

* **WARNING:** not compatible with standard receptacles, requires NEMA5-20R wall receptacle.



X10 Carrier Current Compatible

Specifications	
Voltage Ratings	US 120 Volt, single phase (one hot leg & a neutral leg tied to earth ground at service entrance). Will operate over a voltage range of 85 - 175 volts with Spectrum WVR technology (MCOV=175Vac). Full load regulation 1%. Check line wiring for hot/neutral reversal prior to connecting this filter. Hot/neutral reversal is a critical safety issue and will prevent this product from functioning effectively.
Operating Temperature Range	0-40 deg. C
Technology	Spectrum WVR® Wide Voltage Range & Total Surge Cancellation
Mode	Mode 1 applications, L-N (ground wire protection)
Safety Certifications	CSA 22.2 No. 8-M1986, UL 1283 5 th edition, UL 1363.
Limiters	Series surge reactor current limiter; cascaded, auto-tracking dual polarity dynamic surge and noise sensing; bi-modal dynamic filtering. Parameters optimized for switch-mode power supply protection.
Dynamic filtering Onset	172 volts nominal, 2 volts above peak line voltage (auto-tracking- WVR).
Max. Surge Voltage Let-through*	20 Volts above peak line voltage @ 6,000 Volts, 3,000 Amps for ANSI C62.41 Category B3/C1 Combination Wave.
Max. Applied Pulse Voltage	6,000 volts (1.2 x 50 μs – ANSI C62.41 Combination Wave)
Max. Applied Pulse Current	>100,000 amperes applied (unlimited due to internal current limiting) (8 x 20 μs).
Joule Rating	Not applicable to this technology. No MOV's to wear out.
Endurance Rating	1,000 worst case pulses: ANSI C62.41, Category B3/C1 pulses (6,000 Volts, 3,000 Amperes); >10,000 pulses at 4,000 Volts; >100,000 pulses at 2,000 Volts.
Filter Slew Rate	5,000 volts/μs disturbance reduced to 35 v/μs within AC power wave envelope; 10.0 v/us outside the power wave envelope.
EMI-RFI Filter Response	Bi-directional, wave tracking: With 50 ohm Rgen., load: 7 kHz @ 3 dB; 25 dB @100 kHz; 38 dB @300 kHz.

* Note: Surge voltage let-through is the peak voltage that exceeds the power line peak voltage.

100% Surge Protection, 0% Failure • Are you Zero Surge protected?

Zero Surge Inc. • 889 State Route 12 • Frenchtown, NJ 08825 • Tel.: 908-996-7700 • Fax: 908-996-7773

URL: www.ZeroSurge.com • Email: info@zerosurge.com

8r_t120_v2.doc 4/26/10